AGENDA

CALIFORNIA TRAFFIC CONTROL DEVICES COMMITTEE (CTCDC)

December 5, 2002 MEETING-(916) 654-4715 111Grand Avenue (Parkview Rm. # 15-700), Oakland, 94623

TIME 9:00 AM

Estimated Time

ORGANIZATION ITEMS

| 1. | INTR | ODUCTION | | 9:00 |
|-----------|--|--|--|-------|
| 2. | APPR | OVAL OF MINUTES (August 22, 2002 MEETING) | | 9:05 |
| 3. | PUBL | IC COMMENTS | | 9:10 |
| | Matters For item consider of five (| ime, members of the public may comment on any item not appearing on presented under this item cannot be discussed or acted upon by the Commens appearing on the agenda, the public is invited to make comments at the red by the Committee. Any person addressing the Committee will be lim 5) minutes so that all interested parties, have an opportunity to speak. At ddress, and business or organization for the record. | mittee at this time time the item is nited to a maximu | m |
| AGEN | NDA IT | EMS | | |
| 4. | Prior to traffic c | IC HEARING adopting rules and regulations prescribing uniform standards and specific ontrol devices placed pursuant to Section 21400 of the California Vehiclement of Transportation is required to consult with local agencies and hold | e Code (CVC), th | |
| | 02-7 | 5 5 | (Continued) (Meis) | 9:30 |
| | 02-8 | | (Continued) (Meis) | 10:00 |
| 5. | REQU | JEST FOR EXPERIMENATION | | |
| | 02-10 | ` , | (Continued) (Larsen) | 10:30 |
| | 02-14 | | (Introduction) (Mansourian) | 11:00 |
| | 02-15 | | (Introduction) (Meis) | 11:30 |
| | Lunch | Break | 12:15- | 1:15 |
| | 00-3 | | (Final Report) (Meis) | 1:15 |

| 10. | NEXT | MEETING | | |
|-----|-------|--|----------------------------------|------|
| 9. | C0RR | ESPONDENCES/MISCELLANEOUS | | |
| | 01-11 | Portable or Temporary Speed Display Sign (If the speed feedback sign is a traffic control device or not) | (Continued) (Meis) | |
| 8. | TABL | ED ITEMS | | |
| | 02-9 | Mandatory Requirement Of Accessible Pedestrian Signals (update by Larsen) | (Continued) (Larsen) | 4:15 |
| | 00-1 | Bicycle Pavement Markings (Update by the City Consultant on Methodology to conduct exp.) | (Continued) (Tanda) (Borstel) | 4:00 |
| | 02-13 | Proposed Changes To Chapter 9 -Traffic Signals and Lighting (Update by Caltrans) | (Continued) (Fisher) | 3:45 |
| | 99-11 | MUTCD Adoption By Caltrans (Update by Caltrans) | (Continued) (Meis) | 3:15 |
| 7. | INFO | RMATIONAL ITEMS | | |
| | | Two Days Meeting | (Introduction) | 3:00 |
| | 02-16 | Traffic Signal Warrants 1 & 2 (Footnotes were not included in the 1996 Publication) | (Introduction) (Babico) | 2:30 |
| | 02-12 | When Children Are Present (R72) Sign (Update by Caltrans) | (Continued) (Meis) | 2:15 |
| 6. | DISC | USSION ITEMS | | |
| | 99-18 | Ground Mounted LED Lights On Stop Bars (Experiment Agency-City of Anaheim) | (Final Report) (Meis) | 1:45 |

ADJOURN

11.

CTCDC AGENDA December 5, 2002 Page 3 of 27

ITEM UNDER EXPERIMENTATION

99-10 TACTILE PEDESTRIAN INDICATORS

(Folkers)

(Experiment Agency-The City of Los Angeles)

Status: No update received.

(Fisher)

99-12 SPEED STRIPING FOR SMART CROSSWALKS

(Meis)

(Experiment Agency-Caltrans D7)

Status: Contract has been awarded and Construction will begin shortly.

99-13 ILLUMINATED PAVEMENT MARKERS ON

(Meis)

MEDIAN BARRIERS (Experiment Agency-Caltrans D7)

Status: The project has not been funded yet.

00-1 BICYCLE PAVEMENT MARKING

(Banks)

(Experiment Agency-City of San Francisco)

Status: The city has received approval to hire a consultant to do the study.

00-6 PEDESTRIAN COUNTDOWN SIGNAL HEADS

(Banks)

(Experiment Agency-City of San Francisco)

Status: No further update, the interim report was submitted during the 01/31/02 meeting.

00-8 PEDESTRIAN COUNTDOWN SIGNAL HEAD

(Tanda)

(Experiment Agency-City of San Jose)

Status: The City of San Jose has submitted the final study report during

the May 2002 meeting. The Committee allowed continues use of the devices until to reach

a final decision.

00-9 PEDESTRIAN COUNTDOWN SIGNAL HEAD

(Tanda)

(Experiment Agency-City of Stockton)

Status: City is working on the final report.

01-3 PEDESTRIAN COUNTDOWN SIGNAL HEADS

(Fisher)

(Citywide Experiment request by the City of Fountain Valley)

Status: The City has submitted their final report to the Committee and has received approval to expand the experimentation as a citywide.

01-4 TACTILE PEDESTRIAN INDICATORE WITH AUDIBLE

(Tanda)

INFORMATION (Experiment request by the City of Santa Cruz)

Status: No update.

01-7 PEDESTRIAN COUNTDOWN SIGNAL HEAD

(Tanda)

(Experiment Agency-City of Oakland)

Status: The city has received approval from the HHWA and working to acquire funds in the FY 2002-03 budget.

01-9 IN-ROADWAY WARNING LIGHTS AT R/R CROSSINGS

(Meis)

(Experiment requests by CPUC in cooperation Kern Co. & City of Fresno)

Status: CPUC is in process to hire consultant firm to conduct a study.

PEDESTRIAN COUNTDOWN SIGNAL HEAD 02-2

(Tanda)

(Experiment Agency-City of Berkeley)

Status: The installation of the PCSHs will start later part of the year 2002.

PEDESTRIAN COUNTDOWN SIGNAL HEADS 02-4

(Larsen)

(Experiment request by the County of San Luis Obispo)

STATUS OF CALTRANS ACTION ON PAST ITEMS

Item 90-7 BICYCLE SIGNAL HEADS (BSH)

The Traffic Manual will be changed to reflect the BSH warrants, so that the public agencies will be able to use the Warrants to install these devices on their roadways.

Item 93-18 CROSSWALKS, SEQUENTIAL LIGHTING (In-Roadway Warning Lights (IRWL) at Crosswalks)

Caltrans developing Standard Special Provisions (SSP) for the IRWLs

Item 99-3 AUDIBLE PEDESTRIAN SIGNAL POLICY

Caltrans will work with the CTCDC, the California Council of the Blind (CCB) and with individuals who are interested in this item to resolve along with the Agenda Item 01-5, "Accessible Pedestrian Signals."

Item 01-1 U-TURN SIGNAL HEADS INDICATOR

Caltrans will develop appropriate standards to ensure visibility and make the U-turn signal head indicator an official traffic control device by inclusion in the Caltrans Traffic manual.

Item 01-6 SUPPLEMENT SIGNS ON CHANNELIZERS Caltrans will work with the Committee on this item.

Item 00-4 USE OF RAISED PAVEMENT MARKERS IN TRANSVERSE PATTERN Caltrans will take appropriate action on the recommendation made by the Committee.

Item 01-5 ACCESSIBLE PEDESTRIAN SIGNALS


Caltrans will take appropriate action to adopt the MUTCD verbiage into the Traffic Manual.

Item 02-3 RIGHT EDGELINE

Caltrans will take appropriate action on the recommendation made by the Committee.

02-7 PUSH BUTTON FOR CROSSWALK WARNING LIGHT, WATCH FOR TRAFFIC (R62E)

P 1 of 1 The following is a revised sign message as suggested during the August 22, 2002 meeting.



CTCDC AGENDA December 5, 2002 Page 7 of 27


02-8 Fines Higher (Red Light Violation) Fine Sign

P 1 of 1

The following is a layout and policy for the "Red Light violation" sign

POLICY: SR58

The RED LIGHT VIOLATION \$_____ FINE sign (SR58) may be used in advance of signalized intersections where a local agency has adopted an ordinance setting a specific fine amount for red light violations within it's jurisdiction. This sign may be placed on State highways with an Encroachment Permit when requested by the local agency.



CTCDC AGENDA December 5, 2002 Page 8 of 27

02-10 PEDESTRAIN COUNTDOWN SIGNAL HEADS

P 1 of 1

During the May 8, 2002 meeting, Committee members suggested placing PCSHs on the agenda for the August 2002 meeting to discuss reports submitted by various agencies on the ongoing experimentation. The Committee believes that there is a demand to install these devices. The final reports submitted by the City of Fountain Valley, the City of San Jose and partial study presented by the City of San Francisco indicated that the devices were proven helpful in improving the pedestrian crossings.

During the August meeting, item was deferred until the December meeting.

02-14 SPEED FEEDBACK (Radar Speed) SIGN

P 1 of 4





COUNTY OF MENDOCINO DEPARTMENT OF TRANSPORTATION

340 LAKE MENDOCINO DRIVE UKIAH, CALIFORNIA 95482-9432 (707) 463-4363 FAX (707) 463-5474

5 September 2002

FUNCTIONS Administration & Business Services

Airports County Surveyor Engineering Land Improvement Roads and Bridges

Page 1 of 4

Mr. Davinder Singh Executive Secretary for the CTCDC - MS 36 California Department of Transportation P.O. Box 942874 Sacramento, CA 94274-0001

PROPOSAL FOR EXPERIMENTAL USE OF A NON-STANDARD TRAFFIC CONTROL **DEVICE - ELECTRONIC SPEED DISPLAY SIGNS**

The Mendocino County Department of Transportation (MCDOT) requests permission to conduct an experiment using Electronic Speed Display Signs as non-standard traffic control devices to determine their effectiveness in reducing vehicle speeds in rural school zones.

1. PROBLEM STATEMENT

The most frequently reported collision factor on the Mendocino County Maintained Road system is unsafe speed for conditions. The County is particularly concerned about speeding in school zones on some of our busier rural roads. Several schools are adjacent to collectors that carry commute traffic during the same time students are going to and from school. We frequently receive calls from school officials and parents concerning motorists who fail to observe the posted 25 MPH speed limit in school zones when children are present. Previous efforts to slow traffic in school zones has had little effect.

According to statistical data from the State Office of Traffic Safety (OTS), based on population Mendocino County has the 21st worst accident rate for pedestrians overall and the 37th worst for children under fifteen. OTS has awarded MCDOT a grant to purchase Electronic Speed Display Signs for installation at selected school zones. Distribution of the funds is contingent upon our receiving approval from the California Traffic Control Devices Committee to use these experimental devices.

F:\Shared\WP\SHF\OTS\CTCDCexperimental.doc

Page 2 of 4

2. PROPOSED SOLUTION

To reduce the hazard to students from speeding vehicles, Electronic Speed Display Signs will be installed at the boundaries of three school zones to alert drivers to the speed of their vehicles.

3. OBJECTIVE

The objective of this experiment is to determine the effectiveness of Electronic Speed Display Signs at reducing vehicle speeds in rural school zones when children are present.

4. EXPERIMENT SCHEDULE

- Pre-Installation Evaluation Period......October and November 2002
- Installation......December 2002
- Experiment Period......January to June 2003
- Evaluation Period.....July to September 2003

Thank you for considering our request for experimental designation. If you have any questions, comments or suggestions, please call me at (707)-463-4351. Additional contact information is provided in the attached detailed proposal.

Yours truly,

Stephen Ford, RCE Civil Engineer

Attachment

cc: DOT File 12-11

F:\SharedWP\SHF\OTS\CTCDCexperimental.doc

Page 3 of 4

PROPOSAL TO THE CALIFORNIA TRAFFIC CONTROL DEVICES COMMITTEE FOR EXPERIMENTAL USE OF A NEW TRAFFIC CONTROL DEVICE : ELECTRONIC SPEED DISPLAY SIGNS

SCOPE

The Mendocino County Department of Transportation (MCDOT) proposes to install a total of six Electronic Speed Display Signs, two at each of three school zones. We wish to determine the efficacy of such signs in rural settings. Purchase of the signs will be funded by the State Office of Traffic Safety. Installation and evaluation will be by the County Department of Transportation. The tentative locations are:

| SCHOOL | ROAD | FUNCTIONAL CLASS |
|---|------------------------|--------------------|
| Eagle Peak Middle School | CR 237 West Road | Major Collector |
| Potter Valley Elementary & High Schools | CR 245 Main Street | Major Collector |
| Mendocino Elementary School | CR 408 Little Lake Ros | ad Minor Collector |

WORK PLAN

Installation

The Electronic Speed Display Signs will be installed above Installation C school zone signs. They will replace existing Installation C's at the same locations. The units contain their own radar and will be powered by solar power arrays mounted at the top of the posts similar to rural call-box installations.

Evaluation

Effectiveness will be determined by comparing radar speed data gathered at the sites prior to installation with radar data collected during the experiment period listed below.

Schedule

The schedule for testing is:

| Pre-Installation Evaluation Period | October and November 2002 |
|------------------------------------|---------------------------|
| Installation | December 2002 |
| Experiment Period | January to June 2003 |
| | July to September 2003 |

EVALUATION PROCEDURES

The County of Mendocino requests CTCDC approval of the following preliminary evaluation plan. Evaluation procedures may evolve or be supplemented during the test period.

1) Installation Documentation will be prepared by MCDOT personnel.

F:\SharedWP\SHF\OTS\CTCDCexperimental.doc

Page 4 of 4

- Speed data will be collected and analyzed by or under the direction of MCDOT personnel.
- Field observations will be conducted to help evaluate the effectiveness of the installations. Videotaping may be used to document driver response for reporting to the CTCDC and other interested public agencies.

Before and after studies will be conducted at all three sites where the Electronic Speed Display Signs are to be installed. Measures of effectiveness will include:

Radar speed surveys

Evaluation of vehicle/pedestrian and vehicle/vehicle conflicts within the school zone

Evaluation of driver and student responses to the signing.

ADMINISTRATION

Sponsoring Agency: Mendocino County Department of Transportation

Contact Information: Stephen Ford

Civil Engineer

Mendocino County Department of Transportation

tel: (707)-463-4351 fax: (707)-463-5474

e-mail: fords@co.mendocino.ca.us

Manufactures: Vendor(s) to be determined prior to December 2002

CTCDC AGENDA December 5, 2002 Page 13 of 27

02-15 Radar Guided Dynamic Curve warning System

P 1 of 7

ST AT E O F C AL I FORNI A------ BUSI NESS, T RANSP ORT AT I ON A ND H OUSI NG A GENCY GRAY D AVI S. G o vernor

DEPARTMENT OF TRANSPORTATION

50 HIGUERA STREET SAN LUIS OBISPO, CA 93401-5415 TELEPHONE (805) 549-3111 TTY (805) 549-3259 Http://www.dot.ca.gov/dist05

October 9, 2002

Mr. Gerry Meis Office Chief, Signs Delineation and Permit Branch – MS 36 California Department of Transportation 1120 N Street Sacramento, CA 95814

PROPOSAL FOR EXPERIMENTAL USE OF A NON-STANDARD TRAFFIC CONTROL DEVICE – RADAR GUIDED DYNAMIC CURVE WARNING SYSTEM

The California Department of Transportation (Department) requests permission to conduct an experiment using a Radar Guided Dynamic Curve Warning System (DCWS) as a non-standard traffic control device.

1. PROBLEM STATEMENT

Route 17 is a four-lane highway in Santa Cruz County and is the main access from Route 1 in the City of Santa Cruz to the Route 280/880 junction. Route 17 has a rural feel with minimal or no shoulders in some areas. The City of Santa Cruz attracts weekend motorists that are not familiar with the curvature of Route 17. Many motorists heading southbound are descending the summit at high rates of speed and are not able to judge the tight radius curve that follows the tangent. The collision rate for this curve over the last five years has been higher than the statewide average for similar curves. The actual collision rate from January 1, 1997 to December 31, 2001 was 1.99 collisions per million vehicle miles (MVM) traveled while the statewide average for similar curves was 0.83 collisions per MVM (please see the attached collision diagram and data for this curve). A future project in this area will address the geometric deficiencies of the curve, however, the project is limited to shoulder widening and will not occur for a number of years.

2. PROPOSED SOLUTION

The Department wishes to participate in the experimentation of a Radar Guided DCWS. The DCWS would consist of a Changeable Message Sign (CMS), a radar speed detection unit, and a Closed Circuit Television (CCTV) camera. The CMS would display a message similar to "45"

P 2 of 7

MPH Curve Ahead". Using the installed radar, the sign would then switch to "Your Speed, 70 MPH" to warn the driver that they are approaching the curve at a high rate of speed. The DCWS would be operated remotely by the District 5 Transportation Management Center (TMC) in San Luis Obispo. The system would be configured to allow modification of the CMS message by TMC operators. The CCTV camera would be used to verify the CMS functions. Eventually, the Department would like to gain approval for these systems at other locations where driver safety is a concern.

3. OBJECTIVE

The objective of the test will be to determine the effectiveness of the Radar Guided Dynamic Curve Warning System in slowing vehicle speeds and improving driver safety.

4. EXPERIMENT SCHEDULE

Installation May 2003

Experimental Period May 2003 to May 2004
 Evaluation of Results September 2004

Thank you for considering this request for a Radar Guided Dynamic Curve Warning System. Please see the attached letter of support from Linda Wilshusen, Executive Director for the Santa Cruz County Regional Transportation Commission, collision diagram and data, and the attached photos. The Department is looking forward to receiving a response from the Committee. If you have any questions or need further information, please do not hesitate to call me at (805) 549-3017.

Sincerely,

Nevin Q. Sams

District Traffic Safety Engineer

C: Linda Wilshusen, Executive Director, SCCRTC
Captain Christopher Jenkins, Santa Cruz Area CHP
Captain Ed McLaughlin, San Jose Area CHP
Lauren Wonder, Caltrans District 4
John Thomas, Caltrans District 4
Gregg Albright
Alex Kennedy
Mike Galizio
Paul McClintic
Julie Gonzalez

"Caltrans improves mobility across California"

DEPARTMENT OF TRANSPORTATION

P 3 of 7

50 HIGUERA STREET SAN LUIS OBISPO, CA 93401-5415 TELEPHONE (805) 549-3111 TTY (805) 549-3259 http://www.dot.ca.gov/dist05

PROPOSAL TO THE CALIFORNIA TRAFFIC CONTROL DEVICES COMMITTEE FOR EXPERIMENTATION OF A NEW TRAFFIC CONTROL DEVICE: RADAR GUIDED DYNAMIC CURVE WARNING SYSTEM

SCOPE

The California Department of Transportation (Department) proposes an experiment using a Radar Guided Dynamic Curve Warning System (DCWS). The system will be used to slow vehicle speeds and improve driver safety on Route 17 in Santa Cruz County.

The Radar Guided DCWS is proposed as a pilot program and should help to slow vehicle speeds as they began their descent from the summit. The DCWS has been used in other districts within the Department. District 2 currently has 5 such systems in operation. The system consists in general of installing a Light Emitting Diode (LED) Changeable Message Sign (CMS) with an attached radar unit and a Closed Circuit Television (CCTV) camera. Unlike extinguishable message signs, the CMS's can be used to:

- (1) Display Posted Speed
- (2) Display Advised Speed
- (3) Display Driver's Actual Speed
- (4) Display other information such as, "Accident Ahead, Slow Moving Traffic Ahead", etc.

Display

The display is capable of full size static and dynamic graphics and messages. The display will be a minimum size of 1.7 m by 2.9 m and a maximum size of 2.0 m by 3.6 m.

Power Source

The system will operate using a 120 VAC commercial electrical service. The unit will include the required converter to provide reliable DC power to meet the service demands of the sign system. Electrical service to the installation location on Route 17 has already been established.

System Controls

The sign will be controlled by an on-board computer, capable of storing a minimum of 350 messages, 40 pre-programmed graphic messages, 26 graphic displays of traffic control symbols from the Manual of Uniform Traffic Control Devices (MUTCD) and the sign operation software.

CTCDC AGENDA December 5, 2002 Page 16 of 27

Sign Operation Software

P 4 of 7

The sign operation software (SOS) will provide operator interaction with the sign system and will include a modem to allow remote access utilizing a personal computer via a landline telephone.

CCTV

The DCWS will include a CCTV. The CCTV will be used to verify proper functioning of the CMS as well as for the TMC to gather general traffic information.

Radar Speed Detection

The DCWS will include a radar unit consisting of an externally mounted transceiver (gun). The system will have three modes of operation:

- 1. Radar Only Mode: When the system radar trigger speed has been exceeded, the sign system will continuously display a special sequence of messages that have been preprogrammed into the computer. The actual vehicle speed will be optionally displayed along with any warning messages.
- 2. Radar Trip Mode: A normal sequence of pre-programmed messages will be displayed until the radar trigger speed has been exceeded. Once triggered, the sign system will display a special sequence of pre-programmed messages as well as the detected speed of the motorist.
- 3. Radar Disabled Mode: The sign system will continuously display a sequence of messages which have been pre-programmed into the computer without being interrupted by the radar trigger mechanism.

Remote Operation

The remote system will provide two-way, fully functional interaction and allow for controlling and monitoring sign activity without traveling to the sign. The remote communications software package will enable the sign to alert the Traffic Management Center (TMC) of a failure of the sign's operation, and provide the ability to notify a secondary or tertiary host (such as CHP) in the event that the primary host is inactive. This will also allow re-programming of the sign in the event of an overriding emergency situation. The installed CCTV camera will aid in this process and will also allow the TMC to make other observations such as current traffic conditions.

This request is for permission to purchase and install such a system at approximate Post Mile 11.2 on the southbound side of Route 17 in Santa Cruz County. Currently, a 45-MPH oversized sign with flashing yellow beacons exists just south of this location. The existing sign will remain in place at this time, however, the flashing yellow beacons may be removed after further evaluation.

WORK PLAN
P 5 of 7

Installation

The Radar Guided DCWS will be installed on the southbound side of Route 17 at approximate Post Mile 11.2. This location is on the tangent section of the sustained grade off the summit and is where vehicles begin to pick up speed. There is an existing oversized, 45-MPH sign with flashing yellow beacons at this location now. The sign will remain in place at this time, however, the flashing yellow beacons may be removed after further evaluation.

Evaluation

Effectiveness and acceptance will be measured in accordance with the time period and evaluation procedures shown below.

Time Period

The schedule for testing is as follows:

• Pre-Installation Evaluation January to March 2003

• Installation April 2003

• Experimental Period April 2003 to April 2004

• Evaluation of Results August 2004

EVALUATION PROCEDURES

The Department requests that the Committee approve the preliminary evaluation plan outlined below. Other criteria and procedures may evolve during the evaluation period. Any additional methods of evaluation or changes in procedures will be discussed in the scheduled reports submitted to the project sponsor and the Committee.

- 1. Installation Documentation to be prepared by the Department
- 2. Maintenance Recording to be performed throughout the life of the experimentation period. A maintenance log will be created for the DCWS. Periodic inspection will be performed and logged by the Department's maintenance crew or the CHP.
- 3. Before and after collision data will be prepared by the Department's Traffic Safety Division.
- 4. Observations will be conducted to determine the effectiveness of the system. Videotapes and digital photographs may be used to help document the operation of the system and for reporting to the Committee and other interested parties.

Measures of effectiveness and acceptance before and after the testing period may include, but are not limited to the following:

• Comparison of the total number of incidences before the installation with the number of incidences after the installation

P 6 of 7

• Comparison of the number of speeding violations issued before the installation with the number of speeding violations issued after the installation

ADMINISTRATION

Sponsoring Agency: CA Department of Transportation, Traffic Safety, District 5

Contact Information: Dario A. Senor, P.E., Transportation Engineer

50 S. Higuera Street

San Luis Obispo, CA 93401

Tel: (805) 542-4793, Fax: (805) 549-3045 Vendors to be determined by February 2003

Installations: Contractor to be determined

Manufacturers:

| | | REGIONAL TRANSPORTATION COMMISSION SANTA CRUZ, CALIFORNIA 95060-3911 * 831/460-3200 * FAX 831/460-3215 | |
|--|------|--|---------|
| | | June 17, 2002 | |
| SERVET AUTHORITS | П | Gregg Albright, Director Caltrans District 5 | |
| FIGR RESEMBN EMBELLENCHS (SAFE) | 1077 | 50 Higuera Street San Luis Obispo, CA 93401 | |
| FAILTEN L AUTHORITY | | RE: Support for Application to the California Traffic Control Devices Committee for Dynamic Curve Warning Signs on Highway 17 Dear Director Olbright: | e |
| COMMUTE SOLUTIONS | | The Santa Cruz County Regional Transportation Commission (SCCRTC) is pleased with the safety improvements which have been made to Highway 17 through the | 1 |
| | | "Safe on 17" Task Ferce. As you know, one of the suggestions of the "Safe on 17" Task Force was to add dynamic curve warning signs at key locations on Highway I Its our understanding that the District 5 Traffic Operations Division is working on a | 7. n |
| TEMPSFORTWICH POLICY WORKSHOP | | application to the California Traffic Control Devices Committee for permission to deploy the signs. The SCCRTC Traffic Operations System (TOS) Oversight Committee strongly supports the Caltrans District 5 application for deployment of dynamic curve warning signs on Highway 17 and urges the California Traffic Control. | |
| RUDOFF 4 ADMINISTRATION PERSONNEL | | Devices Committee to promptly approve the application. | |
| COMMUNE | | The TOS Oversight Committee has been working with Caltrans Districts 4 and 5, the California Highway Patrol Coastal Division and Gulden Oate Division, local law enforcement and public works departments and community members to improve the | |
| INTERACTICY FECHNICAL MOUSE XXII COMMUTTRE | | operations and safety of our highways through Intelligent Transportation Systems (ITS) applications. Highway 17 has a system of changeable message signs (CMS) and highway advisory radio (HAR) to inform motorists already on the highway about existing incidents. The CMS and HAR system helps reduce secondary incidents and keep incident related congestion to a minimum. A system such as the dynamic curve | 11 |
| BIONCIE COMMETTEE | | warning signs, which has the potential to reduce primary incidents, would complement the existing CMS and HAR system and contribute to a safer highway. | |
| BIDERLY & DISABLED TRANSPORTATION ADVISORY CDAWLETTE | | If there is anything we can do to assist in the approval of the application to the California Traffic Control Devices Committee, please contact me at (831) 460-3213 or Luis Mendez of my staff at (831) 460-3212. | |
| | | Sincerely. | |
| * | | Linda Wilshusen | |
| | | Executive Director | |
| www.sccrtc.or | G | Il halicon 17 dynamics igus doc | |

P 7 of 7



00-3 Jake Brake Sign

P 1 of 2

The City of Auburn submitted a final report to the Committee. The Committee will accept the report and discuss future action. The report is as follows:

CITY OF AUBURN JAKE BRADE SURVEY SUMARY AND RECOMMENDATION

The Auburn Police Department conducted a post-test of trucks using Jake Brakes at the same locations as pre-tests. During random 24 hour periods the total number of trucks were counted including those that used the Jake Brake and trucks that did not. The noise level of each truck was also recorded. No interviews were conducted of truck drivers. Following are the results of the post-test and comparison to the pre-test:

Pre-test Summary Hiway 49

38 trucks measured using Jake Brakes Average dBL = 77 Average dBL between 2300 and 0700 = 81

Trucks using the Jake Brake as % of the total trucks = 21% Trucks using the Jake Brake between 2300 and 0700 = 36%

Post-test Summary Hiway 49

190 trucks were surveyed Average dBL = 73.55 Average dBL between 2300 and 0700 = 67.4

Trucks using the Jake Brake by % = 29% Trucks using the Jake Brake Between 2300 and 0700 - 18.5%

Pre - test Summary of 1-80

1,410 trucks measured using Jake Brakes Average dBL = 77 Average dBL between 2300 and 0700 = 88

Trucks using Jake Brake as % of total trucks = 32% Trucks using Jake Brake between 2300 and 0700 = 56%

Post - test Summary of I-80

559 trucks were surveyed Average dBL = 73.22 Averatage dBL between 2300 and 0700 = 70.84

Trucks using Jake Brake by % = 42% Trucks using Jake Brake 2300 to 0700 by % = 21.2%

P 2 of 2

Neighborhood Interviews

The Police Department conducted random interviews of persons who live in the immediate area of the 1-80 freeway and Hiway 49 most affected by traffic noise. Half of the individuals interviewed said that the noise from Jake Brake use was about the same, and half said that the noise was less.

Conclusion

Information gathered in the post-test survey seems to indicate that the average noise level caused by trucks at both locations surveyed reduced, and the total percentage of trucks using Jake brakes increased. However, there was a substantial drop in both noise level, and trucks using the Jake brake during the hours of 2300 to 0700. This information suggests that there was a significant change during the nighttime possibly attributable to signage posted in the survey areas.

RECOMMENDATION

From the results of the post – test it is recommended that signage regarding Jake Brake use is posted in area's where Jake Brake noise most affects residential areas during nighttime hours.

CTCDC AGENDA December 5, 2002 Page 22 of 27

99-18 Ground Mounted LED Lights On Stop Bars

P 1 of 1

The City of Auburn submitted a final report to the Committee. The Committee will accept the report and discuss future action.

CTCDC AGENDA December 5, 2002 Page 23 of 27

DISCUSSION ITEMS

P 1 of 3


02-12 When Children Are Present (R72) Sign

The following is a text from the California vehicle Code (CVC) Section 22353 (b):

(B) When approaching or passing a school building or the grounds thereof, contiguous to a highway and posted with a standard "SCHOOL" warning sign, while children are going to or leaving the school either during school hours or during the noon recess period. The prima facie limit shall also apply when approaching or passing any school grounds which are not separated from the highway by a fence, gate or other physical barrier while the grounds are in use by children and the highway is posted with a standard "SCHOOL" warning sign. For purposes of this subparagraph, standard "SCHOOL" warning signs may be placed at any distance up to 500 feet away from school grounds.

The CVC allows installation of signs for differing hours, such as, "going to School", noon recess hours", and "leaving hours" or "school hours" from beginning to end. This is also consistent with the MUTCD.

The following two alternatives are consistent with the current CVC: Alternative 1 P 2 of 3



WHILE CHILDREN
ARE GOING TO
OR LEAVING
SCHOOL & DURING
NOON RECESS

Alternative 2 P 3 of 3



02-16 Traffic Signal Warrant No. 1& 2

1996 Traffic manual

| raffic Manual | TI | RAFFIC SIG | NALS A | ND LIC | SHTING | | | |
|---------------------------------------|---------------------------------------|---|------------------------------|-----------------|------------------------|------------------|------------------|--------------|
| | | F FRAFFIC S | igure 9 IGNAL |)-1 WARE | RANTS | | | |
| DIST CO | RTE K | PM | | | | | | |
| Major St: | | | 370000 | Critical A | pproach Speed | | | km/h |
| Critical speed of major | or street traffic | > 64 km/h | op. ——— | | | AL (R) AN (U) | | |
| VARRANT 1 - Minimun | Nehicular Vo | olume | | | SATISFIED | 2.7 | ES N | Table (75.7) |
| | | QUIREMENTS IN BRACKETS) | | 80% | SATISFIED | Y | ES 🗆 N | 0 ⊔ |
| | UR | UR | ž | 9 | , , | , , | 7 | |
| APPROACH LANES | 1 | 2 or more | | 1 | | | , | lour |
| Both Apprchs. Major Street | 500 350 (400) (280) | 600 420 (480) (336) | | | | | | |
| Highest Approh. Minor Street | 150 105 (120) (84) | 200 140 (160) (112) | | | | | | |
| VARRANT 2 - Interrupt | MINIMUM RE | QUIREMENTS IN BRACKETS) | | | SATISFIED SATISFIED | 160 | ES□ NO ES□ NO | |
| 2 | U R | UR | | . 2 | | | | |
| APPROACH LANES | 1 | 2 or more | | // | | | + | Hour |
| Both Apprchs. Major Street | 750 525 (600) (420) | 900 630 (720) (504) | | 16 5/ | 6 | 130 | Ge 9te | |
| Highest Apprch. Minor Street | 75 53 (60) (42) | 100 70 (80) (56) | | | | al. | | |
| VARRANT 3 - Minimun | n Pedestrian ' | Volume | | 100% | 6 SATISFIED | | YES 🗆 N | ю 🗆 |
| F | REC | UIREMENT | | | FUL | FILLED | 03 | |
| Pedestriar for each o hour; AND | f any four hours | ng the major stree or is 190 or more | et is 100 or i during any | more one | Yes 🗆 | No | | |
| There are stream of | less than 60 ga adequate length | ps per hour in the n for pedestrians t | major stre | et traffic D | Yes 🗌 | No | | |
| The neare than 90 m | | along the major st | treet is grea | ter | Yes 🗆 | No | | |
| The new traffic flow | raffic signal will on the major si | not seriously disr treet. | upt progres | sive | Yes 🗆 | No | | |

The satisfaction of a warrant is not necessarily justification for a signal. Delay, congestion, confusion or other evidence of the need for right-of-way assignment must be shown.

1991 Traffic manual

| - | | - | - | - | | | | - | TIN | - | - | | | | | | |
|----------|--|---|---|--|--|--|--|--|------------------------------------|--------------|-------------|-------------|--|---|------|------|----|
| | | Т | RAF | FIC S | igu IGN | re 9- AL V | 1 NAF | RRA | AN | TS | | | | | | | |
| DIST | CO RTI | E F | PM. | | | CAL | K _ | | | | 7. | _ [| ATE. | _ | | | ph |
| r St | | _ | | | | | _ | Critic | al A al A | ppro | ach S | beed | \equiv | | | 760 | ph |
| Critical | speed of majo | r street | traffic | > 40 mg | ph | | | | | | or | 1 | RURA | L (R) |) | | |
| In bulk | t up area of iso | lated co | mmun | ity of < 1 | 0,000 | pop. | i | | | | | , | JRBA | N (U | 1) | | |
| | IT 1 - Minimu | | | | | | | 1 | 7.7.7.7 | | ATISI | | | | | 0 [| |
| Annan | | MINIM | M REQ | UIREMEN N BRACK | NTS | | | | 809 | % S | ATISI | IED | YE | 5 L | 7 14 | 0 [| 1 |
| | | U | R | | R | | , | 191 | | , | , | 1 | 1 | 000 | , | | |
| F | APPROACH LANES | 1 | | 2 or m | | / | / | / | 1 | | _ | 1 | 1 | 1 | | Hour | |
| | Both Apprehs. | 500 | 350 (280) | | 420 | | | | | | | | _ | | | | |
| | Major Street | | | | (336) | | _ | - | _ | | | | | | | | |
| | Major Street Highest Approh. Minor Street * * NOTE: Heav | 150 (120) ier left t | 105 (B4) urn mo | 200 (160) vernent 1 | 140 (112) from k | | treet i | | 100 | 1% S | SATIS | FIED | YE | S | JN | 100 | |
| | Highest Approb. Minor Street * * NOTE: Heav | 150 (120) ier left t | urn mo | 200 (160) | t40 (112) from k | | treet i | | 100 | 1% S | | FIED | YE | S | JN | 0 | |
| | Highest Approb. Minor Street * * NOTE: Heav | 150 (120) ier left t | 105 (B4) urn mo of Cor | 200 (160) wement t | t40 (112) from k | | treet i | | 100 | 1% S | SATIS | FIED | YE | S | JN | 0 | |
| | Highest Approch. Minor Street * * NOTE: Heav NT 2 - Interru APPROACH | 150 (120) ier left t ption MINEM (80% S | urn mo | 200 (160) wement 1 ntinuou ouireme in Braci | trom k s Tra NTS KETS) | | treet i | | 100 | 1% S | SATIS | FIED | YE | S | JN | 0 | |
| | Highest Approb. Minor Street * NOTE: Heav NT 2 - Interru APPROACH LANES Both Approbs. | 150 (120) ier left t ption MINEM (80% S | of Cor | 200 (160) wement 1 ntinuou ouireme in Braci | trom M s Tra ents (ETS) | | treet i | | 100 | 1% S | SATIS | FIED | YE | S | JN | 10 [| |
| | Highest Approb. Minor Street * NOTE: Heav NT 2 - Interru APPROACH LANES Both Approb. Major Street Highest Approb | 150 (120) Ser left t sption MINIM (80% S U | 105 (84) uurn mo of Cor uum RE HOWN R 1 1 525 (420) | 200 (160) Wernent 1 ntinuou DUREME IN BRACI 2 or 1 900 (720) 100 (60) | 140 (112) from M s Tra (NTS (ETS) P more 630 (804) 70 | ffic | / | - | 100 BC | 9% S 0% S | SATIS | FIED | YE | s C | | Hou | |
| | Highest Approb. Minor Street * * NOTE: Heav NT 2 - Interru APPROACH LANES Both Approbs. Major Street | 150 (120) Ser left t sption MINIM (80% S U | 105 (84) uurn mo of Cor uum RE HOWN R 1 1 525 (420) | 200 (160) Wernent 1 ntinuou DUREME IN BRACI 2 or 1 900 (720) 100 (60) | 140 (112) from M s Tra (NTS (ETS) P more 630 (804) 70 | ffic | / | - | 100 BC | 9% S 0% S | SATIS | FIED | YE | s C | | Hou | |
| VARRA | APPROACH LANES Both Approhs. Major Street * * NOTE: Heav | 150 (120) Ser left t sption MINIM (80% S U 750 (600) 750 (600) Vier left | 105 (B4) urn mo of Cor um Rei iHOWN 1 1 525 (420) 53 (42) turn m | 200 (160) Wernent I OUIREME IN BRACI 2 or 1 900 (720) 100 (80) | 140 (112) from M s Tra (NTS KETS) H more (804) 70 (56) t from | ffic Major \$ | / | - | 100 BC | 1% S 0% S | SATIS | FIED | YE YE | opos |] N | Hou | |
| VARRA | Highest Approb. Minor Street * NOTE: Heav NT 2 - Interru APPROACH LANES Both Approb. Major Street Highest Approb | 150 (120) Ser left t sption MINIM (80% S U 750 (600) 750 (600) Vier left | 105 (B4) urn mo of Cor um RESHOWN 1 525 (420) 53 (42) turn m edestr | 200 (160) Wement 1 Intinuou DUIREME IN BRACH 2 or 1 900 (720) 100 (80) Novement | 140 (112) from M s Tra NTS (ETS) P more (500 (504) 70 (55) t from lume | ffic Major \$ | / | - | 100 BC | 1% S 0% S | SATIS | hasin | YE YE | es [|] N | Hou | |
| VARRA | APPROACH LANES Both Approhs. Major Street APPROACH LANES Both Approhs. Major Street * NOTE: Hea ANT 3 - Minin | 150 (120) iter left to ption MINIM (80% S U 750 (600) 75 (60) wier left | 105 (B4) urn mo of Cor um RE HOWN RE RE HOWN RE RE RE RE RE RE RE RE | 200 (160) Wement 1 Intinuou DUIREME IN BRACT 2 or 1 900 (720) 100 (80) Novement 1 Vo | 140 (112) from k s Tra NTS (NTS (SETS) P 630 (504) 70 (55) t from lume | Major S | Street s 100 | inclu | 100 BC | 1% S 0% S | n LT-F | hasin | YE YE | S C S C S S C S S C S S S S S S S S S S | O N | Hou | |
| VARRA | APPROACH LANES Both Approha. Major Street * APPROACH LANES Both Approha. Major Street * NOTE: Head ANT 3 - Minim Pedestrial for each c hour; and | 150 (120) ier lett t ption MINIM (80% S U 750 (600) 75 (60) wier left num Provolumos any to | 106 (B4) uurn mee of Cori Cori Cori Cori Cori Cori Cori Cori | 200 (160) Wement Intinuou DUIREME IN BRACK 2 or 1 900 (720) 10 | 140 (112) from N s Tra ENTS (ETS) P FOR (S04) 70 (55) t from lume MENT (MENT (MEN | Major Street is | Street s 100 | inclu or m any t | 100 BC ded | whee | n LT-F | hasin | YE YE | S C S C S S C S S C S S S S S S S S S S |] N | Hou | |
| VARRA | APPROACH LANES Both Approhs. Major Street * * NOTE: Heav NT 2 - Interru APPROACH LANES Both Approhs. Major Street Highest Approh Mnor Street * NOTE: Hea ANT 3 - Minim Pedestria for each c hour, and There are | MINIM (80% S U 750 (600) 75 (60) vier left to any for a deep to fade | 105 (84) uurn moot Cori of Cori et HHOWN REI 1 525 (420) 1 53 (42) 1 turn m edestr RE ne cros | 200 (160) wement intinuou DUIREME IN BRACH 2 or 1 900 (720) 100 (80) overnent rian Vo QUIREME sing the irs or is 1 gaps per ength for | 140 (112) from k s Tra s Tra ENTS (504) 70 (55) t from (504) 45) t from (504) 45) t from (504) 650 or (504) 6 | Major street is more d | Street st | or many or any or street | 100 BC | whee | n LT-F | hasin FUL | YE YE | ES C | O N | Hou | |
| VARRA | APPROACH LANES Both Approb. Major Street * NOTE: Heav NT 2 - Interru APPROACH LANES Both Approb. Major Street Highest Approb Minor Street * NOTE: Hea ANT 3 - Minim Pedestria for each of hour; and | MINIM (80% S 750 (600) 75 (60) Vier left to recommend any for any for added to feet; ar | 105 (84) uurn moot Cori Cori Market | 200 (160) wement intinuou DUIREME IN BRACH 2 or 100 (720) 100 (60) rian Vo OUIREM eing the ins or is 1 gaps per ength for | 140 (112) rorm N S Tra S | Major street is more d in the matrians ajor street | s 100 buring najor s to cro | or many or man | 100 BC added 100 acres traffind er | whee | SATIS SATIS | hasing FUL: | YE Y | es C | | Hou | |